



OP-70 HEAVY DUTY OIL BOOM



OSPICO OP-70 Oil Boom is suitable for permanent and or semi-permanent deployment to recover oil spill.

The ballast, anchor point, connectors, bolts, and nuts are all made from non-corrosive and salt water resistant materials to ensure the longevity its parts.

Each part can be repaired separately due to the detachability of the float and ballast. Separates waste and oil spill.

A highly effective water pollution control designed for permanent deployment in locations with a risk of spill or for emergency response situation.

HEAVY DUTY OIL BOOM MATERIAL

Component	Material	Advantage
FLOAT	Fiber glass / HDPE-filled with polyurethane foam	Hydrocarbon and chemical resistant. Incorporated handle in design
SKIRT	Heavy Duty PVC Reinforced Polyester Coated	UV Resistant and easy to clean
BALLAST	Galvanized Chain	Non-Corrosive and salt water resistant
CONNECTOR	ASTM F962 SS 316	Non-Corrosive and easily joined without additional tool
ACHORPOINT	Stainless Steel 316	Non-Corrosive and salt water resistant
BOLT AND NUT	Stainless Steel 316	Non-Corrosive and salt water resistant
CONNECTOR PIN	Stainless Steel 316	Non-Corrosive and salt water resistant
IMPACT PROTECTOR	Heavy Duty Rubber	Floating Bumper



Handgrip

Polyurethane Foam

Solid molded fiber glass

UV Resistant and easy to clean



TECHNICAL DATA

Type	HEAVY DUTY
Model	OP-70
Section Length (m)	10-50
Float Dimension (cm)	Length 70 Width 30
Over all skirt strength (lbs)	4000 - 16000
Recommended application	Onshore and Bay
Recommended installation	Permanent, Semi-Permanent and Emergency
Deployment method	Workboat and Shoreline
Boom over all (cm)	70

PT . BLUE OCEAN SEJAHTERA

Nifarro Park, ITS Tower Unit 1208, Jl. Raya Pasar Minggu Kav. 18 Jakarta 12510

Phone +62 21 22792650, +62 21 22792651

Email : marketing@blueoceansejahtera.com

