



OSSKIM ODS 10-T



TECHNICAL DATA			
Dimension		Material	
Length	47,2 inch	Body	Stainless Steel
Width	40 inch	Fitting	PVC
Height	22 inch	Floating	Aluminum
Weight (Max)	38 kgs	Disc	P.M.M.A
Disc	0,25 m	Scraper	PTFE
Operating draft	15 inch	Connection	Quick Release Coupling
Standard Accessories		Hose Kit	
1 x Lifting	3 x Hose	Suction Hose	15 m (50 feet) Ø 2 inch Flexible hose with camlock
		Discharge Hose	15 m (50 feet) Ø 2 inch Flat hose with camlock
Tool Kit	1 set	Hydraulic Hose	2 x 15m x Ø 3/8 inch with Quick Release Coupling
Cover	1 set		
Disc			
No of Disc	6		
Disc Speed	Variable speed 0 - 66 rpm Max		
Driven	Hydraulic lobe Motor		
Transfer pump			
Type	Self priming		
Capacity	10 ton / hours		
Driven	Hydraulic motor		
Power Pack		Power Pack Dimension	
Starting Operation	Electric Start	Length	1100 mm
Power	7,6 kw	Height	700 mm
Frame Finish	Epoxy Paint	Width	700 mm
		Weight	250 kgs

The OSSKIM ODS 10T is a disc skimmer designed to overcome oil spill at territorial water with a small water current or Zero Emission Zones (diesel free operations).

It is suitable for both permanent and emergency operations.

Disc rotation speed is adjustable depending on the amount of oil spill and is controlled from the hydraulic power pack with diesel activator.

It lifts oil by 98% with a capacity of 10 ton/hour



PT . BLUE OCEAN SEJAHTERA

Nifarro Park, ITS Tower Unit 1208, Jl. Raya Pasar Minggu Kav. 18 Jakarta 12510

Phone +62 21 22792650, +62 21 22792651

Email : marketing@blueoceansejahtera.com