



OSSKIM OWS 30-T



TECHNICAL DATA			
Dimension		Material	
Length	35.43 inch	Hover	Stainless Steel 316
Width	27.56 inch	Fitting	PVC
Height	23.62 inch	Floating	Fiber Glass
Weight (Max)	85 kg	Base Frame	Stainless Steel
Hover Dimension	23.62 x 23.62 inch	Mounting Float	Aluminum Pipe SCH 80
Operating draft	6.0 inch	Connection	Quick Release Coupling
Standard Accessories		Hose Kit	
1 x Lifting	3 x Hose	Discharge Hose	15 m (50 feet) Ø 2 inch Flat hose with camlock
Tool Kit	1 set	Hydraulic Hose	4 x 15m x Ø 3/8 inch with Quick Release Coupling
Cover	1 set		
Transfer pump on board			
Type	Self priming		
Capacity	30 ton / hours		
Driven	Hydraulic motor		
Power Pack		Power Pack Dimension	
Starting Operation	Electric Start	Length	1100 mm
Power	7,6 kw	Height	700 mm
Frame Finish	Epoxy Paint	Width	700 mm
	Weight		250 kgs



OSSKIM OWS 30-T can be used to lift all types of oil from ports, rivers, territorial water, and coast in a large quantity.

3 floats are used to balance the draft of the skimmer.

The float and hover draft automatically adjusts itself to accommodate various thickness of the spill on the water surface.

The OSPICO Power Pack is used to supply hydraulic power to the OSSKIM skimmers or other equipment.

The power pack features an instrument panel with a hand starter (electric starter also available for hazardous conditions).



PT . BLUE OCEAN SEJAHTERA

Niffaro Park, ITS Tower Unit 1208, Jl. Raya Pasar Minggu Kav. 18 Jakarta 12510

Phone +62 21 22792650, +62 21 22792651

Email : marketing@blueoceansejahtera.com